Printing date 08/27/2015

Reviewed on 08/26/2015

# **1** Identification

- · Product identifier
- · Trade name: RED DIAMOND
- · Details of the supplier of the safety data sheet
- *Manufacturer/Supplier:* Patton Industrial Service 1005 Aero Drive Shreveport, LA 71107
- Information department: (318) 227-4000 • Emergency telephone number: Infotrac; (800) 535-5053 (North America) (352) 323-3500 (International)

## **2** Hazard(s) identification

· Classification of the substance or mixture

GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

*Eye Dam. 1* H318 Causes serious eye damage.

- · Label elements
- *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). *Hazard pictograms*



· Signal word Dang	er
· Hazard-determini	ng components of labeling:
sodium hydroxide	
disodium metasilic	ate
NP-9 (4-nonyl phe	nol 9 mole E.O.)
· Hazard statements	
H314 Causes sever	re skin burns and eye damage.
· Precautionary stat	ements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P260	Do not breathe dusts or mists.
P303+P361+P353	<sup>3</sup> IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P405	Store locked up.
	(Contd. on page 2)



Printing date 08/27/2015

Reviewed on 08/26/2015

#### Trade name: RED DIAMOND

P501	(Contd. of page 1) Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classificatio	0
· NFPA rating	
	Health = 3
	Fire = 0
30	$e^{2}$ Reactivity = 0
· HMIS-rating	gs (scale 0 - 4)
HEALTH 4	Health = 4
FIRE 0	Fire = 0
	Reactivity = $0$
• Other hazard	ds
· Results of Pl	BT and vPvB assessment
• <b>PBT:</b> Not ap	
• vPvB: Not ap	

## **3** Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
1310-73-2	sodium hydroxide	2.5-10%
6834-92-0	disodium metasilicate	2.5-10%
	Alcohol Ethoxylate Phosphate (Proprietary)	≤ 2.5%
	NP-9 (4-nonyl phenol 9 mole E.O.)	≤ 2.5%
111-76-2	2-butoxyethanol	≤ 2.5%

#### **4** First-aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Remove contact lenses if able to do so.
- Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing:

A person vomiting while lying on their back should be turned onto their side.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· Most important symptoms and effects, both acute and delayed

Corrosive and extremely irritating to all tissues. Nausea

Gastric or intestinal disorders Thirst

Thirst

Cramp • **Danger** 

Danger Danger of a get

Danger of gastric perforation. Large doses may result in red blood cell hemolysis.

(Contd. on page 3)

<sup>·</sup> Description of first aid measures

USA

(Contd. of page 2)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/27/2015

Reviewed on 08/26/2015

#### Trade name: RED DIAMOND

#### • Indication of any immediate medical attention and special treatment needed Medical supervision for at least 48 hours.

#### **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### **6** Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
   Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

#### • **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

# 7 Handling and storage

- · Precautions for safe handling
- *Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.*
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Unsuitable material for receptacle: glass or ceramic. Unsuitable material for receptacle: aluminium.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

<sup>-</sup> USA

Printing date 08/27/2015

Reviewed on 08/26/2015

## Trade name: RED DIAMOND

(Contd. of page 3)

. Cont	(Contd. of page 3 rol parameters
	ponents with limit values that require monitoring at the workplace:
	-73-2 sodium hydroxide
	Long-term value: 2 mg/m <sup>3</sup>
	Ceiling limit value: 2 mg/m <sup>3</sup>
	<i>Ceiling limit value: 2 mg/m<sup>3</sup></i>
	76-2 2-butoxyethanol
	Long-term value: 240 mg/m <sup>3</sup> , 50 ppm
I LL	Skin
REL	Long-term value: 24 mg/m <sup>3</sup> , 5 ppm
	Skin
TLV	Long-term value: 97 mg/m <sup>3</sup> , 20 ppm
	BEI
Ingr	edients with biological limit values:
-	76-2 2-butoxyethanol
	200 mg/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Butoxyacetic acid with hydrolysis
Addi	tional information: The lists that were valid during the creation were used as basis.
Imma Wash Avoit Avoit <b>Brea</b> In ca respi	away from foodstuffs, beverages and feed. ediately remove all soiled and contaminated clothing. I hands before breaks and at the end of work. I contact with the eyes. I contact with the eyes and skin. thing equipment: se of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure u ratory protective device that is independent of circulating air. ection of hands:
un.	Protective gloves
Due chen	glove material has to be impermeable and resistant to the product/ the substance/ the preparation. to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the ical mixture.
Mate	tion of the glove material on consideration of the penetration times, rates of diffusion and the degradation <i>rial of gloves</i> rene gloves
	or PE gloves
	le rubber, NBR
	rubber, BR
	relection of the suitable gloves does not only depend on the material, but also on further marks of quality and a free manufacturar to manufacturer. As the product is a preparation of several substances, the resistance is a preparation of several substances.

varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

(Contd. of page 4)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/27/2015

Reviewed on 08/26/2015

#### Trade name: RED DIAMOND

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Not suitable are gloves made of the following materials: Leather gloves
- Strong gloves
- · Eye protection:

Tightly s

Tightly sealed goggles

· Body protection: Alkaline resistant protective clothing

# 9 Physical and chemical properties

<ul> <li>Information on basic physical and c</li> <li>General Information</li> </ul>		
· Appearance:		
Form:	Liquid	
Color:	Clear	
· Odor:	Mild	
· Odour threshold:	Not determined.	
· pH-value at 20 °C (68 °F):	14	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	$> 100 \ ^{\circ}C \ (> 212 \ ^{\circ}F)$	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
• Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17 mm Hg)	
· Density at 20 °C (68 °F):	1.05 g/cm <sup>3</sup> (8.762 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
		(Contd. on page

USA

Printing date 08/27/2015

Reviewed on 08/26/2015

#### Trade name: RED DIAMOND

	(C	ontd. of page 5)
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	2.0~%	
Water:	86.9 %	
VOC content:	2.0 %	
	21.0 g/l / 0.18 lb/gl	
Solids content:	11.1 %	
• Other information	No further relevant information available.	

## 10 Stability and reactivity

#### · Reactivity

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions Reacts with strong acids and oxidizing agents. Corrodes aluminium.
- *Conditions to avoid No further relevant information available.*
- · Incompatible materials: No further relevant information available.
- *Hazardous decomposition products:* Sodium Oxides Carbon monoxide and carbon dioxide

## **11 Toxicological information**

· Information on toxicological effects

#### • Acute toxicity:

· LD/LC50 values that are relevant for classification:

1310-73-2 sodium hydroxide

Oral LD50 2000 mg/kg (rat)

#### · Primary irritant effect:

• on the skin: Strong caustic effect on skin and mucous membranes.

 $\cdot$  on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

111-76-2 2-butoxyethanol

## · NTP (National Toxicology Program)

no ingredient above de minimis level is listed

(Contd. on page 7)

3

USA

Printing date 08/27/2015

Reviewed on 08/26/2015

Trade name: RED DIAMOND

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · **Remark:** Harmful to fish
- $\cdot$  Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## **13 Disposal considerations**

- · Waste treatment methods
- *Recommendation:* Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number	
· DOT, IMDG, IATA	UN3266
· UN proper shipping name	
$\cdot DOT$	Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide)
· IMDG, IATA	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (SODIUM
,	HYDROXIDE)

Printing date 08/27/2015

Reviewed on 08/26/2015

Trade name: RED DIAMOND

	(Contd. of page
· Transport hazard class(es)	
·DOT	
the second se	
CORROSIVE	
· Class	8 Corrosive substances
· Label	8
· IMDG, IATA	
The second se	
V	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Alkalis
• Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
• Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L
2	On cargo aircraft only: 30 L
· IMDG	
· Limited quantities (LQ)	1L
• Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN3266, Corrosive liquid, basic, inorganic, n.o.s. (Sodiur
	hydroxide), 8, II

# **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 9)

USA

Printing date 08/27/2015

Reviewed on 08/26/2015

#### Trade name: RED DIAMOND

	(Contd. of page 8		
· Section 313	3 (Specific toxic chemical listings):		
111-76-2	2-butoxyethanol		
7758-29-4	pentasodium triphosphate		
· TSCA (Tox	cic Substances Control Act):		
1310-73-2	sodium hydroxide		
6834-92-0	) disodium metasilicate		
9016-45-9	NP-9 (4-nonyl phenol 9 mole E.O.)		
111-76-2	2 -butoxyethanol		
7758-29-4	pentasodium triphosphate		
78330-20-8	Ethoxylated Isodecyl Alcohol		
7732-18-5	water, distilled, conductivity or of similar purity		
· Proposition	· Proposition 65		
· Chemicals	known to cause cancer:		
None of the ingredients is listed.			
· Chemicals known to cause reproductive toxicity for females:			
None of the	r ingredients is listed.		
· Chemicals	known to cause reproductive toxicity for males.		
None of the ingredients is listed.			
· Chemicals known to cause developmental toxicity:			
None of the	r ingredients is listed.		
· Carcinoger	iic categories		
· EPA (Envi	· EPA (Environmental Protection Agency)		

· EPA (Environmental Protection Agency)	
111-76-2 2-butoxyethanol	
· TLV (Threshold Limit Value established by ACGIH)	
111-76-2 2-butoxyethanol	
· NIOSH-Ca (National Institute for Occupational Safety and Health)	

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

· Hazard-deter	rmining components of labeling:
sodium hydro	pxide
disodium me	tasilicate
NP-9 (4-non	yl phenol 9 mole E.O.)
· Hazard state	ments
H314 Causes	s severe skin burns and eye damage.
· Precautional	ry statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
	v

(Contd. on page 10)

NL

AЗ

Printing date 08/27/2015

Reviewed on 08/26/2015

#### Trade name: RED DIAMOND

	(Contd. of page 9)
P260	Do not breathe dusts or mists.
P303+P361+	-P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+	-P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
~	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 08/27/2015 / -

· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 USA